

## CLAIMS

I claim:

- 5 1. A method of aligning a first image to a second image, comprising:  
determining a first alignment approximation, based on distances between one or more  
points in the first image and the second image,  
aligning the second image to the first image, based on the first alignment approximation,  
to form an initially aligned second image,  
determining a second alignment approximation, based on distances between one or more  
points in the first image and the initially aligned second image, and  
10 aligning the second image to the first image, based on a combination of the first and  
second alignment approximations.
2. The method of claim 1, wherein  
aligning the second image to the first image based on the combination of the first and  
second alignment approximations is effected by:  
aligning the initially aligned second image, which is based on the first alignment  
approximation, to the first image, based on the second alignment approximation.
- 20 3. The method of claim 1, wherein  
determining the first alignment approximation is based on a low-resolution representation  
of the first and second images, and  
determining the second alignment approximation is based on a higher-resolution  
representation of the first and second images.
- 25 4. The method of claim 1, wherein  
determining at least one of the first alignment and second alignment approximations  
includes applying the RANSAC algorithm.

5. The method of claim 1, wherein

determining the first alignment approximation includes an approximation of at least one of a rotation component and a translation component in an image space of the first and second images.

5

6. The method of claim 5, wherein

determining the second alignment approximation includes an approximation of components of a 3x3 homographic matrix.

10

7. The method of claim 1, wherein

determining the second alignment approximation includes an approximation of components of a 3x3 homographic matrix.

8. The method of claim 1, wherein

determining at least one of the first and second alignment approximations includes identifying corners in the first and second images based on a determination of Minimum Intensity Changes at the corners.

09854119 05.1.10.1

9. A method of tracking an object based on a first image and a second image, comprising:  
aligning the first and second images to form a set of aligned images, and  
detecting motion by comparing the set of aligned images,  
wherein

5 aligning the first and second images includes:  
determining a first alignment approximation, based on distances between one or  
more points in the first image and the second image,  
aligning the second image to the first image, based on the first alignment  
approximation, to form an initially aligned second image,  
10 determining a second alignment approximation, based on distances between one  
or more points in the first image and the initially aligned second image, and  
aligning the second image to the first image, based on a combination of the first  
and second alignment approximations.

10. The method of claim 9, wherein  
determining the first alignment approximation is based on a low-resolution representation  
of the first and second images, and  
determining the second alignment approximation is based on a higher-resolution  
representation of the first and second images.

11. The method of claim 9, further including  
identifying the object in the set of aligned images based on color matching.

12. The method of claim 9, further including  
25 determining a location of the object in each image of the set of aligned images, and  
determining a movement of the object by comparing the location of the object in each  
image.

13. A motion detecting system comprising:

a processor that is configured to:

align a first image and a second image, to form a set of aligned images, by:

determining a first alignment approximation, based on distances between

one or more points in the first image and the second image,

aligning the second image to the first image, based on the first alignment approximation, to form an initially aligned second image,

determining a second alignment approximation, based on distances between one or more points in the first image and the initially aligned second image, and

aligning the second image to the first image, based on a combination of the first and second alignment approximations; and

compare the set of aligned images to identify motion of objects within the first and second images.

14. The motion detecting system of claim 13, wherein

the processor is configured to:

determine the first alignment approximation by processing a low-resolution representation of at least one of the first and second images, and

determine the second alignment approximation by processing a higher-resolution representation of the first and second images.

15. The motion detecting system of claim 13, further including

one or more cameras for producing the first and second images.

16. The motion detecting system of claim 13, further including

a memory for storing a representation of a target image, and

wherein

the processor is further configured to identify a target within the set of aligned images, based on the representation of the target image.

17. The motion detecting system of claim 16, wherein  
the representation of the target image is a characterization based on color content of the  
target image.

5 18. The motion detecting system of claim 13, further including  
determining a location of an object in each image of the set of aligned images, and  
determining a movement of the object by comparing the location of the object in each  
image.

10 19. The motion detecting system of claim 13, wherein  
determining the first alignment approximation includes an approximation of at least one  
of a rotation component and a translation component.

20. The motion detecting system of claim 19, wherein  
determining the second alignment approximation includes an approximation of  
components of a 3x3 homographic matrix.

09654-119-051101  
701750-15850